

Gas Generator Sets

H54GV I Bore: 540 mm, Stroke: 600 mm

Main Data

Speed	600 rpm		600 rpm	
Frequency	60 Hz		50 Hz	
	Eng. (kW)	Gen. (kW)	Eng. (kW)	Gen. (kW)
12H54GV TSTC ¹⁾	16,800	16,380	16,800	16,380
14H54GV TSTC	19,600	19,110	19,600	19,110
16H54GV TSTC	22,400	21,840	22,400	21,840

Based on alternator efficiency of 97.5 %.

1) TSTC : Two Stage Turbo Charger

Heat Rate & SFOC (100% Load)

Speed	600 rpm
Heat Rate	7,090 kJ/kWh
Electrical Efficiency	50.2


*) Note :

1) Reference condition based on ISO 3046/1

2) Fuel gas based on natural gas, Lower Heating Value 36MJ/Nm³, methane number Min. 80


Specific Lubricating Oil Consumption

Lub. Oil: 0.5 g/kWh



Dimension & Weight

	Dimension (mm)				Dry mass (ton)	
	A	B	C	H	Engine	GenSet
12H54GV TSTC	12,511	4,638	17,149	7,994	294.0	381.0
14H54GV TSTC	13,661	4,582	18,243	7,994	324.0	421.0
16H54GV TSTC	15,086	4,757	19,843	8,383	361.0	467.0



Remarks

- 1) Depending on alternator.
- 2) Without common base frame.
- 3) With common base frame & alternator (Maker: Hyundai Electric).

Note) All dimensions and weight are approximate value and subject to change without prior notice.



SOAR POWER GROUP
[Http://www.soarpower.com](http://www.soarpower.com)
 E-mail: sale@soarpower.com
 Hotline: +86-4008111308