


## DIMENSIONS (mm) AND WEIGHTS (t)

Type	A	B	C	D	E	F	G	H	t
<b>6 M 20 C</b>	941	4049	988	520	1596	630	330	2099	10.7
<b>8 M 20 C</b>	941	4935	988	520	1731	630	330	2236	14.0
<b>9 M 20 C</b>	941	5176	988	520	1731	630	330	2236	15.0

A: Wet sump (standard)

F: Dry sump (special request)




## TECHNICAL DATA

Type	Output range		Speed	Mean eff. pressure	Mean piston speed	Bore	Stroke	Spec. fuel consumption	
								100%	85%
	kW	hp	rpm	bar	m/s	mm	mm	g/kWh	g/kWh
<b>6 M 20 C</b>	1020	1390	900	24.1	9.0	200	300	186	186
	1140	1550	1800	24.2	10.0	200	300	190	189
<b>8 M 20 C</b>	1360	1850	900	24.1	9.0	200	300	186	186
	1520	2070	1800	24.2	10.0	200	300	190	189
<b>9 M 20 C</b>	1530	2080	900	24.1	9.0	200	300	186	186
	1710	2330	1800	24.2	10.0	200	300	190	189

Specific lubricating oil consumption 0.6 g/kWh, ± 0.3 g/kWh

LCV = 42700 kJ/kg, without engine-driven pumps, tolerance 5%



Engine centre distance: 2010 mm

Removal of cylinder liner:

in transverse direction 1910 mm

in longitudinal direction 2085 mm

Nozzle position:

ask for availability

Engine with turbocharger at free end available, ask for dimensions