

DK-26e



主要参数 PRINCIPAL PARTICULARS

Fuel oil/燃油		HFO (重油) 700~180mm ² /s/50℃		Diesel oil/ 船用柴油	
Speed/转速	r/min	720	750	720	750
Frequency/频率	Hz	60	50	60	50
6DK-26e	Eng.kW	1850	1850	1850	1850
	Gen.kW	1740	1740	1740	1740

注：基于电机效率为94%，具体机组功率由发电机效率决定。
 Note: Based on nominal generator efficiencies of 94%. The final power of D/Gs is determined by generator efficiency.
 具体尺寸根据具体电机型号确定，以下尺寸仅供参考
 The below dimension: only reference. The final dimensions are determined by the type of generator.

Specifications/主要规格

结构 Configuration		直列 In-line	
缸径 Bore	mm	260	
冲程 Stroke	mm	380	
转数 Eng.revs.	r/min	720	750
活塞速度 Piston speed	m/s	9.1	9.5
平均有效压力 Mean eff. press	MPa	缸数/No. of cyl.	
		6	6
		2.36	2.36
爆发压力 Max. combust press	MPa	17.7	17.7

尺寸与重量 DIMENSION & WEIGHT

毫米:mm

尺寸标记 Mark	A	B	C	D	E	F	G	H	J	净重(大约) NET weight(appr)		
										Eng	Gen	Total
机型 Model												
6DK-26e	6465	3310	1990	1190	5400	1200	1970	1580	2470	16.0	10.1	30.0

